AMH120.5EC - AMH240.5EC

Public Address - Amplifiers and Audio Sources



-
- Mixer amplifier with 5 inputs, available in 2 powers: AMH120.5EC (120W) & AMH240.5EC (240W)

GENERAL FEATURES

-
- 5 inputs with separate volume control
- Mixed or priority mode inputs
- Input 1 overrides all other inputs by remote control
- Input 2 overrides inputs 3, 4, 5 by vox or remote control
- Adjustable levels for Aux 2, 3, 4 and 5
- Bass and treble separate controls
- Phantom power supply for Microphone and 24VDC for paging desk
- Sliding AUX/MIC switches on rear panel
- XLR, RCA, and plug-in screw connectors for inputs
- 0dB output on RCA connector
- 50V- 70V -100V line outputs using press connector
- Led VU-meter
- Protection against overload and short circuits
- Easy configuration
- Smaller size
- High reliability
- High quality connnectors
- Specific options
- Multichannel amplifiers in 2U cabinet
- Compliance : EN6065, CEM, RoHs
- Measurement as per IEC-268-3 Standard

TECHNICAL CHARACTERISTICS

Inputs:	5
Power:	120 W (AMH120.5EC), 240W (AMH240.5EC)
Loudspeaker Output:	100 - 70 - 50 V
Mains Input:	230 V AC
Dimensions:	440 x 88 x 283 mm
Weight:	11 Kg (120W) - 17 Kg (240W)
Colours:	Black

INSTALLATION

Rack mount (2U) or stand alone

These features given for information only. Sonelco.com reserve the right to make changes without notice in order to improve the product. More information: (+34) 976 259 135 / (+34) 609 719 454 / sat@sonelco.com