

AMH120.5EC - AMH240.5EC

Public Address - Amplifiers and Audio Sources



• Mixer amplifier with 5 inputs, available in 2 powers: AMH120.5EC (120W) & AMH240.5EC (240W)

GENERAL FEATURES

- 5 inputs with separate volume control
- Mixed or priority mode inputs
- Input 1 overrides all other inputs by remote control
- Input 2 overrides inputs 3, 4, 5 by vox or remote control
 Adjustable levels for Aux 2, 3, 4 and 5
- Bass and treble separate controls
- Phantom power supply for Microphone and 24VDC for paging desk
- Sliding AUX/MIC switches on rear panel
- XLR, RCA, and plug-in screw connectors for inputs
- 0dB output on RCA connector
- 50V- 70V -100V line outputs using press connector
- Led VU-meter
- Protection against overload and short circuits
- Easy configuration
- Småller size
- High reliability
- High quality connnectors
- Specific options
- Multichannel amplifiers in 2U cabinet
- Compliance : EN6065, CEM, RoHs
- Measurement as per IEC-268-3 Standard

TECHNICAL CHARACTERISTICS

Inputs:

Power: 120 W (AMH120.5EC), 240W (AMH240.5EC)

Loudspeaker Output: 100 - 70 - 50 V **Mains Input:** 230 V AC

Dimensions: 440 x 88 x 283 mm

Weight: 11 Kg (120W) - 17 Kg (240W)

Colours: Black

INSTALLATION

Rack mount (2U) or stand alone