



PCP1232

Background Music - Controls and Modules (45x45mm)

Digital adjustment control, 2 stereo channel and message receipt. Infrared receiver, controlled by P4804 remote control (optional). with functions of superbass, sleep, adjustment of bass, treble, balance and ideal sound.

GENERAL FEATURES

Electronic ON / OFF switch.
ON /Sleep/ Sb luminous indicator, bicolour LED type.
Key depression luminous indication (Vol+, Vol- and SCAN).
52-step digital volume control with selected position memory.
Integrated audio processor.
Superbass.
SCAN function.
Selection of two music channels, with light indicating channel selected.
Voltage telecontrol.
External channel input (walkman).
Direct access to stations via control P4804.
Jumper for selection of mono output. For this type of installations place the jumper M/S.

TECHNICAL CHARACTERISTICS

Music channels:	2
Power:	1 + 1 W RMS
Output Impedance:	8 Ohm.
Maximum Power:	1.5 + 1.5 W RMS
Maximum Current	Terminal 3: 1 A
Frequency Response:	80 Hz. - 21 KHz. (-3dB)
Signal/Noise Ratio:	> 87 dB
Sensitivity:	1,45 V
Mains Input:	16 V DC
Nominal Input Level for Warning Switching:	15 V
Nominal Output Level for Calls:	15 V
Maximum Consumption:	420 mA
Standby Consumption:	30 mA
Dimensions:	45x45x45 mm.
Weight:	58 gr.
Colours:	PCP1232-01 (White), PCP1232-02 (Graphite), PCP1232-10 (Ivory), PCP1232-12 (Silver)

INSTALLATION

Universal box. Require cover frame.